


GROUP

2 ROUND AND FLAT EARTH METAL STRAPS, ROUND CABLES AND BARS




Galvanised metal strap	Item	Dim. mm	Sect.mm ²	±m/coil	Pcs per box
------------------------	------	---------	----------------------	---------	-------------



Hot-galvanised steel metal strap by means of dipping , with a zinc coat of 500 gr/m2. Packaging: coils of ± 50 kg In accordance with 64.8 ; 11.1 ; 81.1 IEC Standards.

PIAT-35K	30x3,5	105	60	1
PIAT-4K	40x3,0	120	52	1
PIAT-44K	40x4,0	160	40	1


Galvanised metal strap	Item	ø in mm	Sect.mm ²	±m/coil	Pcs per box
------------------------	------	---------	----------------------	---------	-------------



Hot-galvanised steel metal strap by dipping process , with a zinc coat of 500 gr/m2. Packaging: coils ± 50 kg In accordance with 81.1 IEC Standards.

PIAT-3K	30x3,0	90	70	1


Galvanised metal strap	Item	ø in mm	Sect.mm ²	Weight in Kg	Pcs per box
------------------------	------	---------	----------------------	--------------	-------------



Hot-galvanised steel metal strap by dipping process , with a zinc coat of 500 gr/m2. Packaging: 10 m. with 2 holes of Ø 11mm and with 2 galvanised bolts and nuts of 10 mm at the ends. In accordance with 11.1 ; 81.1 IEC Standards.

PIAT-3R	30x3	90	7,30	1

Zinc strap	Item	Holes in mm	Length in m.	Pcs per box
------------	------	-------------	--------------	-------------



Drilled zinc strap coils around 12 Kg. Section 46x2.5 mm. Enel matricule 239805.

PIAT-Z	ø 17 and button hole 33x23 mm	21 c.a.


Running out of stock

GROUP

2 ROUND AND FLAT EARTH METAL STRAPS, ROUND CABLES AND BARS



Hot-galvanised steel continuous round cable	Item	ø in mm	Sect.mm ²	±m/coil	Pcs per box
---	------	---------	----------------------	---------	-------------



Hot-galvanised steel continuous round cable, with a zinc coat of 350 gr/m², in accordance with IEC 7.6 Standards.

Packaging: coils about 40 kg for Ø 8 mm


In accordance with 64.8 ; 81.1 IEC Standards.

coils about 47 kg for Ø 10 mm

In accordance with 64.8 ; 11.1; 81.1 IEC Standards.

TT-8K	8	50	100	1
TT-10K	10	78	75	1

Copper round cable	Item	ø in mm	Sect.mm ²	±m/coil	Pcs per box
--------------------	------	---------	----------------------	---------	-------------



Soft copper round cable. Packaging: coils about 22 kg

In accordance with 64.8 ; 11.1; 81.1 IEC Standards.



TT-8R	8	50	50	1
-------	---	----	----	---

Bare copper plait	Item	ø in mm	Sect.mm ²	ø plaits in mm	Weight in Kg	Skein m.
-------------------	------	---------	----------------------	----------------	--------------	----------




Bare copper plait class 2. Quality: 99.99% pure. Supplied in skein of 100m. Sections of 35 mm² and over are appropriate for pick-up and leadin elements; as horizontal earth plate

In accordance with 64.8 ; 11.1; 81.1 IEC Standards.



TR25	6,40	25	7 x Ø 2,14	24,00	100
TR35	7,56	35	7 x Ø 2,52	32,00	100
TR50	9,00	50	7 x Ø 3,00	45,00	100

Spiral cable	Item	ø in mm	Sect.mm ²	ø strands in mm	Ultimate load Kg	Weight Kg	Skein m
--------------	------	---------	----------------------	-----------------	------------------	-----------	---------



Hot-galvanised steel spiral cable (IEC 7.6) core made of 19 strands (12+6+1).

Appropriate for pick-up and leadin elements; as horizontal earth plate. Strength wires per unit 120 Kg/mm².

Supplied by skein

In accordance with 64.8 ; 11.1; 81.1 IEC Standards.

FZC10	10	60,0	2,0	6500	49,00	100
FZC11	11	72,2	2,2	7900	60,00	100

Round bar	Item	Material	ø in mm	Sect.mm ²	±Kg/bar	Pcs per box.
-----------	------	----------	---------	----------------------	---------	--------------



Round bar of 4 m.

In accordance with IEC Standards.

T-8BK	Hot-galvanised steel	8	50	1,6	1
T-10BK	Hot-galvanised steel	10	78	2,5	1
T-8BRK	Copper	8	50	1,6	1
T-10BRK	Copper	10	78	2,5	1